

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275
PRODUCT HAZARD RATINGS (NFPA): - Health = 1, Fire = 1, Reactivity = 0, Protective Equipment = *B
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

***** SECTION I *****
NETWORK SERVICES COMPANY TELEPHONE NUMBER FOR INFORMATION : 1-847-803-4920
1550 Bishop CT
Mount Prospect, IL 60056

DATE PRINTED : 11/29/01 NAME OF PREPARER : Ron Cepa

***** SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION *****

Chemical Names (LD50-Oral Rat)	SEC 313	Exposure Limits TLV/TWA	SARA Title III PEL	ACGIH	OSHA	% By Wt.
-----------------------------------	---------	----------------------------	-----------------------	-------	------	----------

2 Butoxy Ethanol (CAS# 111-76-2)		148mg/kg	Yes	25ppm	25ppm	4.85
Alkyl Dimethyl Amine Oxide (CAS# 7128-91-8)		NE	-	NE	-	1.0-5.0
Quarternary Ammonium Chloride (CAS# 5197-80-8)		620mg/kg	-	NE	-	0.1-0.5
Sodium Ethylene Diamine Tetraacetate (CAS# 64-02-8)		3030mg/kg	-	NE	-	1.0-5.0
Liquified Petroleum Gas (CAS# 68476-85-7)		NE	-	1000	1000	1.0-5.0

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: None

***** SECTION III - PHYSICAL CHARACTERISTICS *****

Boiling Point: NA Vapor Pressure (psig): 115 @130F Specific Gravity (H2O=1): <1.0
Solubility/Water: >10% Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Foaming spray / floral-ammonia odor.

***** SECTION IV - FIRE AND EXPLOSION HAZARD DATA *****

Aerosol Flammability: This product is considered to be non flammable as described in 16CFR 1500.45.
Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

***** SECTION V - REACTIVITY DATA *****

Stability: Stable Hazardous Polymerization: NA
Incompatibility (Materials to Avoid): Strong oxidizers, heat and open flame.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and additional toxic chemicals may be formed in small amounts.
Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

