

ITEM NUMBER: 271 - INSECT KILLER
VERSION 2 EFFECTIVE DATE: 3/3/00 SUPERCEDES: 8/20/97
IDENTITY (As Used On Label and List): INSECT KILLER

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275
PRODUCT HAZARD RATINGS (HMIS): - Health = 1, Fire = 1, Reactivity = 0, Protective Equipment = B
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

***** SECTION I

NETWORK SERVICES COMPANY
1550 Bishop CT
Mount Prospect, IL 60056

TELEPHONE NUMBER FOR INFORMATION : 1-847-803-4920

DATE PRINTED : 11/29/01 NAME OF PREPARER : Ron Cepa

***** SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION *****

Chemical Names (LD50-Oral Rat)	SEC 313	Exposure Limits TLV/TWA	SARA Title III PEL	ACGIH	OSHA	% By Wt.
-----------------------------------	---------	----------------------------	-----------------------	-------	------	----------

Resmethrin (5-(phenylmethyl)-3-
furanyl) methyl-2,2-dimethyl-3-
(2-methyl-1-propenyl)

cyclopropanecarboxylate (CAS# 10453-86-8)	NA	NA	YES	ND	ND	0.20
Esbiothrin (CAS# NA)	NA	NA	NA	ND	ND	0.10
Piperonyl Butoxide (CAS# 51-03-6)	NA	NA	YES	ND	ND	0.40
Liquified Petroleum Gas(CAS# 68476-85-7)	NA	NA	NA	1000ppm	1000ppm	19.00

Balance of ingredients are non-hazardous or below reportable quantities.

Components Listed As A Suspected Carcinogen: None

***** SECTION III - PHYSICAL CHARACTERISTICS *****

Boiling Point: NA Vapor Pressure (psig): 110@130F Specific Gravity (H2O=1): 1
Solubility/Water: Emulsible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Aerosol spray with characteristic odor.

***** SECTION IV - FIRE AND EXPLOSION HAZARD DATA *****

Aerosol Flammability: Product does not need to be labeled as flammable as described in 40 CFR 156.10.
(Under certain conditions this product may burn.)

Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5

Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct
flame or heat contact should be cooled with water to prevent weakening of container structure.

***** SECTION V - REACTIVITY Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or
sparks. Dropping of containers may cause bursting.

