

MATERIAL SAFETY DATA SHEET
ITEM NUMBER: 296 - CLAIRE BIG JINX III
VERSION 2 EFFECTIVE DATE: 01/25/01 SUPERCEDES: 04/23/98 PREPARED BY: Ron Cepa
Section(s) Revised: HMIS, II, III, IV, V, VI, VIII
IDENTITY (As Used On Label and List): BIG JINX III

MSDS 296

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275
PRODUCT HAZARD RATINGS (NFPA): - Health = 1, Fire = 2, Reactivity = 1, Protective Equipment = B
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

SECTION I
NETWORK SERVICES COMPANY TELEPHONE NUMBER FOR INFORMATION : 1-847-803-4920
1550 Bishop CT
Mount Prospect, IL 60056

DATE PRINTED : 11/29/01 NAME OF PREPARER : Ron Cepa

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION
Chemical Names CAS # SARA Title III ACGIH OSHA % By Wt.
SEC 313 TLV/TWA PEL

Chemical Names	CAS #	SARA Title III	ACGIH	OSHA	% By Wt.
Synthetic Isoparaffinic hydrocarbon	64742-47-8	No	NE	300 ppm	5-10
Liquefied petroleum gas mixture	See below	No	--	--	10-20
Propane	74-98-6	--	1000 ppm	NE	-
n-Butane	106-97-8	--	600 ppm	NE	-

Balance of ingredients are non-hazardous or below reportable levels.

SECTION III - PHYSICAL CHARACTERISTICS
Boiling Point: NA Vapor Pressure (psig): 110 @ 130F Specific Gravity (H20=1): >1
Solubility/Water: Slight Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): <1

Appearance and Odor: Aerosol spray with characteristic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product does not need to be labeled as flammable as described in 40 CFR 156.10.

Flashpoint: <0F (Propellant); >200F (Concentrate)

Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5

Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA

Incompatibility (Materials to Avoid): Strong oxidizers.

Hazardous Decomposition Products: Carbon monoxide, hydrocarbon vapors.

Conditions to Avoid: Keep away from heat, sparks, and flames. Dropping of containers may cause bursting.

